

LANTZ'S COACHWORKS, INC.

100 S. Kentucky Ave, Evansville, IN 47714

PH.: 812-425-4439

FAX: 812-425-7676

Lantz's Coachworks, Inc
100 S Kentucky Ave
Evansville, IN 47714
Attn: Jim Patton

Quote #JP06-007
June 20, 2006
PH: 812-425-4439
FX: 812-425-7676

Invoice No. _____
Tank S/N: _____
Deposit Amt.: _____
Deposit Date: _____

Chassis Requirements:

Front Axle: 16,000 lb.
Rear Axle: 40,000 lb.
Chassis: Conventional

GAWR: 16,000 lb.
GAWR: 40,000 lb.
GVWR: 56,000 lb.

C/A: 172"
W/B: 240"

Tank:

Model: TTS
Capacity: DBWA-45-4-E
4500 gallons
Compartments: Four (4)
Compartments Sizes: 1500-1000-1000-1000
Pipe Rotation: 1-2-3-4 (L-R)
Tank Spec.: D.O.T. 406
Product: Petroleum
Lbs./Gal.: 6.1 - 7.2 lbs. per gal.
Shell Material: 5454 Aluminum (.180)
Bottom Material: 5454 Aluminum (.312)
Bulkhead Material: 5454 Aluminum (.230)
Head Type: All Double Bulkheads
Head Shape: Wide Oval
Head Size: 63.5" x 95"
Mounting Sills: Aluminum Extrusion (10" x 3-1/2" x 3/8")
Internal Valves: 3" x 2" air operated tee type w/ operator at rear.
Outlet Lines: 2-1/2" stainless steel lines to rear bucket box.
3" to passenger side front terminating in blind TTMA flange.
Outlet Valves: None.
Dome Lids: Betts 16" PAF w/ 10" offset fills.
Vapor Recovery: Prep vapor rail w/ 3-1/2" stubs and victaulic outlets, run 3" vapor stub inside rear canopy.
Skirting: Bolt-on aluminum tandem axle fenders.
Side Cabinets: 72" 2-door aluminum, frame mount.
Lights/Wiring: Betts L.E.D. lights, sealed wiring.
Rear Cabinet: Enclosed w/60" wide overhead door.
Hose Doors: 28" x 28" each side.
Catwalk: None.
Hand Rails: w/ Ladder.
Access: 14" wide grip-strut ladders at rear, both sides.
Paint Specs.: Bright finish aluminum, paint steel parts only.
Overturn Drains: (2) total. One (1) each side at front of tank.

Pumping System:

Dual equipment in rear bucket box. Meters face out rear doors.

Quantity:	Description:
2	Heavy duty "Hot Shift" pto's for manual transmissions w/ rear controls.
2	1-1/4" PTO shaft assembly.
2	Blackmer TXD-2-1/2, 100 gpm pumps w/ strainers.
1	Pump Bracket.
2	2" Total Controls Meters w/ MID:COM Smart Link. Includes (2) e-count registers and 2-stage electronic preset valves.
2	Hannay 12v power hose reel w/E.P. motors and switches.
1	Dual meter installation kit w/ air release tank & meter brackets.
1	1-1/4" x 150' Goodyear hose w/ 1-1/2" OPW automatic nozzle and swivel.
1	1-1/4" x 75' Goodyear hose w/ 1-1/2" OPW automatic nozzle and swivel.
2	2" x 5' swing hose w/ Emco Wheaton "Buckeye" dry break couplers.
1	Set dual system piping material.
4	Betts B-30 swivel spot lights, one (1) each side at rear, facing rear and (1) mounted on rear corner of each side cabinet wired to a single switch in cab.
1	30 gallon flush tank piped back to suction line on diesel side system.
1	Obserview rear vision monitor system w/ CM-560 5.6" color monitor and CC-47-L camera.
4	DOT #1203 decal placards.
1	2A-40BC Fire extinguisher w/ bracket. (Mounted in cab)
1	DOT Triangle flare kit.

Notes / Conditions:

- ~Purchase order required with order, full payment due on completion.
- ~7-year tank shell warranty against leaks, 1-year on equipment.
- ~Quotation good for 30 days.
- ~Additional charge to re-locate exhaust, air drier, battery box, etc.